

HA11 USB Handset

USB handset with PTT button, cradle and base plate

Article Number

01 6511 00500151 (former 6506-011-001-51)



Characteristics

- Dynamic microphone and ear capsule
- Large push-to-talk button
- Heavy base plate for solid stand without screws
- Durable spiral cable
- Cradle without locking mechanism
- Solid plastic housing
- Hook-switch mechanism
- Flame-resistant plastic housing
- Loudspeaker in the cradle

Scope of delivery

- Handset with spiral cable, cradle and 2 m USB type A cable

Options

- Loudspeaker in the cradle
- Cradle with locking mechanism for the handset with release buttons
- Customized HID coding
- [Minor modifications and individual adaptations](#) on request

Application range

- Offices, control centres and control rooms
- Ideal for mobile and fixed installation radio systems

Specifications

General

Housing	PC-ABS plastic, black
Dimensions	Height 95 mm, width 63 mm, depth 213 mm
Weight	980 g (34.5 oz)
Connection	6-wire, halogen-free spiral cable, 2 wires shielded, extension length 1.35 m max., USB Type A cable
Operating elements	1 PTT button (orange, freely programmable), black
Storage temperature	-30 °C to +70 °C (-22 °F to +158 °F)
Operating temperature	-25 °C to +60 °C (-13 °F to +140 °F)

Microphone

Frequency range	200 Hz to 6 kHz at -10 dB
Sensitivity (in LRGP)	1 mV/Pa (-60 dBV/Pa \pm 3 dB)
Impedance	200 Ohm \pm 20 % at 1 kHz
Directivity	Omnidirectional
Operating voltage	5 V USB (DC)

Earpiece

Frequency range	300 Hz to 4 kHz at -10 dB
Sensitivity	26 dBPa/V \pm 3 dB (IEC 3.2 low-leak coupler)
Impedance	300 Ohm \pm 20 % at 1 kHz
Maximum output	10 mW